



**POLYLIGHT  
COLUMNS**

## LISTADO DE COLUMNAS OPTIMIZADAS

MODELO	Altura	Clase	Deformación*	Diámetro base	Diámetro punta	Espesor fuste	Espesor placa base
FVB-03-1-120	3 metros	1	12 cm	120 mm	78 mm	4 mm	20 mm
FVB-03-1-140	3 metros	1	12 cm	140 mm	78 mm	4 mm	20 mm
FVB-04-1-120	4 metros	1	16 cm	120 mm	78 mm	5 mm	20 mm
FVB-04-1-140	4 metros	1	16 cm	140 mm	78 mm	5 mm	20 mm
FVB-05-1-140	5 metros	1	20 cm	140 mm	78 mm	5 mm	20 mm
FVB-05-2-120	5 metros	2	30 cm	120 mm	78 mm	5 mm	20 mm
FVB-06-1-175	6 metros	1	24 cm	175 mm	78 mm	5 mm	30 mm
FVB-06-2-140	6 metros	2	36 cm	140 mm	78 mm	5 mm	30 mm
FVB-06-3-120	6 metros	3	60 cm	120 mm	78 mm	5 mm	30 mm
FVB-07-1-175	7 metros	1	28 cm	175 mm	78 mm	5 mm	30 mm
FVB-07-2-140	7 metros	2	42 cm	140 mm	78 mm	5 mm	30 mm
FVB-07-3-140	7 metros	3	70 cm	140 mm	78 mm	5 mm	30 mm
FVB-08-1-195	8 metros	1	32 cm	195 mm	78 mm	6 mm	30 mm
FVB-08-2-195	8 metros	2	48 cm	195 mm	78 mm	5 mm	30 mm
FVB-08-3-140	8 metros	3	80 cm	140 mm	78 mm	5 mm	30 mm
FVB-09-1-195	9 metros	1	36 cm	195 mm	78 mm	6 mm	35 mm
FVB-09-2-195	9 metros	2	54 cm	195 mm	78 mm	5 mm	35 mm
FVB-09-3-175	9 metros	3	90 cm	175 mm	78 mm	5 mm	35 mm
FVB-10-1-220	10 metros	1	40 cm	220 mm	100 mm	6 mm	35 mm
FVB-10-1-195	10 metros	1	40 cm	195 mm	78 mm	8 mm	35 mm
FVB-10-2-195	10 metros	2	60 cm	195 mm	78 mm	5 mm	35 mm
FVB-10-3-195	10 metros	3	100 cm	195 mm	78 mm	5 mm	35 mm
FVB-11-1-250	11 metros	1	44 cm	250 mm	100 mm	6 mm	45 mm
FVB-11-2-220	11 metros	2	66 cm	220 mm	100 mm	6 mm	45 mm
FVB-11-3-195	11 metros	3	110 cm	195 mm	78 mm	5 mm	40 mm
FVB-12-1-250	12 metros	1	48 cm	250 mm	100 mm	7 mm	45 mm
FVB-12-2-250	12 metros	2	72 cm	250 mm	100 mm	5 mm	45 mm
FVB-12-3-195	12 metros	3	120 cm	195 mm	78 mm	6 mm	40 mm
FVB-13-1-300	13 metros	1	52 cm	300 mm	150 mm	7 mm	45 mm
FVB-13-2-280	13 metros	2	78 cm	280 mm	150 mm	6 mm	45 mm
FVB-13-3-250	13 metros	3	130 cm	250 mm	120 mm	5 mm	45 mm
FVB-14-1-300	14 metros	1	56 cm	300 mm	150 mm	8 mm	45 mm
FVB-14-2-280	14 metros	2	84 cm	280 mm	150 mm	6 mm	45 mm
FVB-14-3-280	14 metros	3	140 cm	280 mm	150 mm	5 mm	45 mm
FVB-15-2-300	15 metros	2	90 cm	300 mm	150 mm	7 mm	45 mm
FVB-15-23-280	15 metros	3	150 cm	280 mm	150 mm	6 mm	45 mm

\*Deformación obtenida para un viento de 29 m/s y un área expuesta al viento de la luminaria de 0,13 m<sup>2</sup>

**POLYLIGHT COLUMNS**

**AB ZETA M&C, S.L. · B92092691 · www.polylightcolumns.com · info@polylightcolumns.com**  
(+34) 986 623 755 · Pque. Empl. O Sobral, 6 FORCADELA 36730, Tomiño (Pontevedra) - Galicia.